

SHIELDCOAT TECHNICAL DATA SHEET

RUSTSHIELD AL



DESCRIPTION

Rustshield AL is a premium, solvent-based coloured acrylic coating specifically designed to restore and protect rusty metal roofs, providing a long-lasting, galvanized-like finish. Its self-priming formulation eliminates the need for separate primers, simplifying application and saving time on the job. Formulated to penetrate and bond directly to metal surfaces, Rustshield AL effectively seals out moisture and prevents further rust development, enhancing the roof's lifespan and appearance.

Viscous liquid - Dries silver


Available in 15L pails




APPLICATION GUIDE

- Rustshield AL is ready to use, with no thinning required, however if desired thin with xylene sparingly.
- Pressure clean the roof with 3000+ psi, taking care to thoroughly rinse the roof at the end.
- Avoid application when temperatures are below 7°C or above 35°C.
- Rustshield AL is designed to be airless sprayed using a 521 or similar spray tip.
- On hot and humid days it may be necessary to increase tip size to 523 or 525 to avoid cobwebbing.
- Allow extra curing time in winter months and do not spray after 2pm where possible.


RUSTSHIELD AL



ADVANCED
ADHESION



SELF
PRIMING



PENETRATES

COVERAGE: 6-7 sqm/Lt

SOLIDS: 20% ave

WFT: 60um

DFT: 20um

TOUCH DRY: 20 Mins

RECOAT: 2 Hours

SHELF LIFE: 24 Months

CLEAN UP: Xylene

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT