

# SHIELDCOAT TECHNICAL DATA SHEET

## RUSTSHIELD

W

### DESCRIPTION

**Rustshield W** is a high-performance, water-based acrylic sealer and primer designed for metal roof substrates. It offers superior protection against rust and provides an ideal base for Roofbond Roof Membrane or Thermobond HRC topcoats. With over 12 years of proven durability, Rustshield W outperforms traditional solvent-based primers and spot treatments. When used with Roofbond or Thermobond HRC, it comes with a 10-year guarantee for long-lasting protection.

**Viscous liquid - Dries grey**


**Available in 15L pails**



### APPLICATION GUIDE

- Rustshield W is ready to use, with no thinning required, however if desired thin with water sparingly.
- Pressure clean the roof with 3000+ psi, taking care to thoroughly rinse the roof at the end.
- Avoid application when temperatures are below 7°C or above 35°C.
- Rustshield W is designed to be airless sprayed using a 521 or similar spray tip.
- Allow extra curing time in winter months and do not spray after 2pm where possible.

## RUSTSHIELD W




ADVANCED  
ADHESION



WATER  
BASED



MAXIMUM  
COVERAGE



HIGH  
OPACITY

**COVERAGE:** 5-6sqm/Lt

**SOLIDS:** 50% ave

**WFT:** 180um

**DFT:** 90um

**TOUCH DRY:** 30 Mins

**RECOAT:** 2 Hours

**SHELF LIFE:** 24 Months

**CLEAN UP:** Water

**DISCLAIMER:** Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT